
Read the Docs Template Documentation

Release 1.0

Read the Docs

Mar 02, 2020

Contents

1	Intro	3
1.1	Overview	3
1.2	Authors	3
1.3	Components	3
2	OpenTileServer	5
2.1	Features	5
2.2	Installation	5
2.3	Options	6
2.4	Examples	6
2.5	Welcome Page	6
2.6	Contribute	7
2.7	Support	7
2.8	License	7
3	Usage	9
4	AcuGIS	11

Contents:

1.1 Overview

This script is for building a basic tile server with OpenStreetMap data

1.2 Authors

- David Ghedini
- Kaloyan Petrov
- Cited, Inc

1.3 Components

<https://www.openstreetmap.org>

<http://www.geofabrik.de/>

<http://mapnik.org/>

<http://openlayers.org/>

<http://leafletjs.com>

<http://www.postgresql.org/>

<http://postgis.net/>

<https://github.com/gravitystorm/openstreetmap-carto>

<https://github.com/mapbox/osm-bright>

This script is for building a basic tile server with OpenStreetMap data.
Only for use on a clean Ubuntu 14, Ubuntu 16, or Ubuntu 18 install!!

2.1 Features

- Load OSM Data
- Load OSM data (city, country, continent or planet).
- Postgres, PostGIS, and osm2pgsql
- Installs Postgres, PostGIS, and osm2pgsql.
- Installs and configures Apache for http or https
- Mapnik, mod_tile, and renderd
- OSM-carto or OSM-bright
- OpenLayer and Leaflet example page.

2.2 Installation

Step 1: Get opentileservr.sh script from GitHub

Step 2: Make it executable:

```
$ chmod 755 opentileservr-ubuntu-xx.sh
```

Step 3 (for non-Latin alphabet)

If using a non-Latin alphabet, uncomment line 24 below if needed:

```
$ export LC_ALL=C
```

See <https://github.com/AcuGIS/opentilesserver/issues/4>

Step 4: Run the script:

```
$ ./opentilesserver-ubuntu-xx.sh [web|ssl] [bright|carto] pbf_url
```

2.3 Options

```
[web|ssl]: 'web' for http and 'ssl' for https  
[bright|carto]: 'carto' for openstreetmap-carto or 'bright' for openstreetmap-bright  
pbf_url: Complete PBF url from GeoFabrik (or other source)
```

2.4 Examples

Load Delaware data with openstreetmap-carto style and no SSL:

```
$ ./opentilesserver.sh web carto http://download.geofabrik.de/north-america/us/  
↪delaware-latest.osm.pbf
```

Load Bulgaria data with openstreetmap-bright style and SSL:

```
$ ./opentilesserver-ubuntu-xx.sh http://download.geofabrik.de/europe/bulgaria-latest.  
↪osm.pbf bright
```

Load South America data with openstreetmap-carto style and SSL:

```
$ ./opentilesserver-ubuntu-xx.sh ssl carto http://download.geofabrik.de/south-america-  
↪latest.osm.pbf
```

2.5 Welcome Page

Once installation completes, navigate to the IP or hostname of your server.

You should see a page as below:



Leafletjs Example



OpenLayers Example

Click on both the OpenLayer and Leaflet Examples and check your installation is rendering

[Produced by AcuGIS. We Make GIS Simple](<https://www.acugis.com>)

[Cited, Inc. Wilmington, Delaware](<https://citedcorp.com>)

2.6 Contribute

- Issue Tracker: github.com/AcuGIS/OpenTileServer/issues
- Source Code: github.com/AcuGIS/OpenTileServer

2.7 Support

If you are having issues, please let us know. We have a mailing list located at: project@google-groups.com

2.8 License

The project is licensed under the BSD license.

CHAPTER 3

Usage

Tile urls have the form ‘`http://host/osm_tiles/{z}/{x}/{y}.png`’:

```
http://192.83.58.10/osm_data/{z}/{x}/{y}.png
```

```
http://domain.com/osm_data/{z}/{x}/{y}.png
```


CHAPTER 4

AcuGIS

AcuGIS
Cited, Inc.